

DOUBLE DOOR PROOFER/RETARDER LRPR2S-HO-C

Construction Features

- ◆ Heavy duty stainless steel exterior with 300 Series stainless steel interior and aluminized steel top
- ◆ Foam-insulated walls, ceiling and door
- ◆ Modular wall and ceiling panels with cam interlocks
- ◆ Tubular heaters; non submerged to extend life
- ◆ Lighted Interior
- ◆ Inner bumpers to protect interior walls and doors
- ◆ Refrigeration system with epoxy-coated evaporator coils and R404A refrigerant

Performance Features

- ◆ Dual purpose, provides both proofing and retarding
- ◆ Rapid responding air-wash heat and humidity system
- ◆ Proofing Temperature Range: 70-120 deg F
- ◆ Retarding Temperature Range: 34-45 deg F
- ◆ Humidity Range: 50-99%
- ◆ Evaporators sized for high humidity levels to prevent drying of product
- ◆ Refrigeration system sized for rapid pull-down
- ◆ PID-type controller design to ensure rapid and accurate response without overshoot

Controls Features

- ◆ Control is mounted in the door at eye level
- ◆ Large LED displays for Time, Temperature, and humidity.



Meets UL 197 and NSF 2 Standards



Model LRPR2S-40 shown (rack not included)

Rack Capacity:

Model	Side Load	End Load	Double
LRPR2S-30HO-C	2	3	N/A
LRPR2S-40HO-C	4	3	2
LRPR2S-50HO-C	4	3	2
LRPR2S-60HO-C	6	6	2
LRPR2S-70HO-C	6	6	2
† LRPR2S-80HO-C	8	6	4
† LRPR2S-90HO-C	8	9	4
† LRPR2S-100HO-C	10	9	4
† LRPR2S-110HO-C	10	12	4
† LRPR2S-120HO-C	12	12	6

† Pre-charged option not available on these models

Short Bid Specification:

Proofer Retarder shall be an **Empire Bakery Equipment Model LRPR2S-__HO-C** (insert 30, 40, 50, 60, 70, 80, 90, 100, 110, or 120 to indicate desired depth). Appliance shall be a double-wide roll-in rack unit, electrically heated with double doors, a quick response air-wash heat and humidity system, high output refrigeration system that includes the solenoid valve(s), expansion valve(s), line dryer(s) and epoxy coated evaporator coils, and modular foam-insulated panel construction. Interior shall be 300 series stainless steel with perimeter bumpers to protect door and walls. Doors shall have a magnetic seal, automatic closers and a full-width protective bar handles. Computerized control shall be door mounted at eye-level with accurate LED displays for Time, Temperature and Humidity. Complete appliance shall have all features listed and, if selected, optional 300-series stainless steel floor and/or 72610-48 water filtration system. **Pre-charged refrigeration shall be optional** (Available up to -70).

Technical Data


DOUBLE DOOR PROOFER/RETARDER LRPR2S-HO-C

Installation Requirements:

- Factory authorized start-up required
- Ships knocked down. Requires on-site assembly
- Appliance is designed to operate at normal room temperatures
- Should not be installed within 4" of oven or other heat source to prevent heat transfer
- Clearance to combustibles is 0" sides and back
- Floor must be level to within 1/8" per foot. Difference for entire floor must not exceed 3/4"
- For installation on non-porous surfaces only

Note: Refrigeration system may require installation by a licensed refrigeration technician

PLEASE NOTE: When ordering precharged unit with ceiling mounted condenser, please add 16.9"



Utility Requirements:

Model	Cooling * 208VAC		Heating * (6.0 kW max) 208-240VAC			Retarder BTU @ 35 deg F
	MCA	MOP	MCA 1 ph	MCA 3 ph	MOP	
LRPR2S-30HO-C	7.4, 1P	15	35	20	50	5500
LRPR2S-40HO-C	7.4, 1P	15	35	20	50	5500
LRPR2S-50HO-C	9.7, 1P	15	35	20	50	6000
LRPR2S-60HO-C	12.7, 1P	20	35	20	50	8600
LRPR2S-70HO-C	12.7, 1P	20	35	20	50	8600
† LRPR2S-80HO-C	17.2, 1P	25	35	20	50	11000
† LRPR2S-90HO-C	17.2, 1P	25	N/A	40	60	11000
† LRPR2S-100HO-C	22.4, 1P	35	N/A	40	60	15600
† LRPR2S-110HO-C	22.4, 1P	35	N/A	40	60	15600
† LRPR2S-120HO-C	21.8, 3P	30	N/A	40	60	21000

* 2 separate electrical supplies required

† Pre-charged option not available on these models

Dimensions:

Dim A (in)	Dim B (in)
29.0	31.0
39.0	41.0
49.0	51.0
59.0	61.0
69.9	71.0
79.0	81.0
89.0	91.0
99.0	101.0
109.0	111.0
119.0	121.0

Shipping Information:

Weight (lbs)		Freight Class
Actual	Shipping	
773	1200	85
841	1282	
899	1454	
967	1536	
1035	1618	
1093	1790	
1039	1872	
1107	1954	
1165	2126	
1233	2208	

Water Quality Requirements:

pH: 7.0-8.5
Total Hardness < 50 ppm
Chlorides < 50 ppm
Total Chlorine < 0.5 ppm
Iron < 0.3 ppm

Water	Drain
1/2" NPT, cold, filtered 0.07 gpm @ 60 psi	3/4" copper, Route to air gap drain